5.5 Dimensional Requirements

5.5.1 Dimensional requirements schedule, principal use buildings

5.5.1	Dimensional requirements schedule, principal use buildings					
	Minimum	Minimum	Minimum	Minimum	Minimum	Maximum
	Lot Size	Lot Frontage	Front Yard	Side Yard Setback	Rear Yard	Building
	(square feet)	(linear feet)	and Street	(linear feet)	Setback	Height
			Line		(linear feet)	(linear feet)
			Setback (a)			
			(linear feet)			
RE	no minimum dimensional requirements					
AF	43,560, plus 22,500 per	150	25	15	30	28
	dwelling unit after first					
AF-2	87,120	200	25	15	30	28
AF-4	174,240	250	25	15	30	28
RS- 1	15,000, plus 5,000 per	100	15	10	30	28
	dwelling unit after 2nd					
RS-2	22,500, plus 5,000 per	150	25	15	30	28
	dwelling unit after first			-		
RB	43,560, plus 22,500 per	200	25	15	30	28
	dwelling unit after first	200	25	10	30	20
NB	10,000	75	15	10	30	28
ND	10,000	73	13	10	30	20
CB	no minimum lot size	no minimum lot	Edge of	0, if there is access to rear of lot over a	15	36
		frontage	sidewalk,	drive at least 12 in width		
		· ·	OR 10 max if			
			no sidewalk			
GB	no minimum lot size	no minimum lot	25	0, if there is access to rear of lot over a	30	36
		frontage		drive at least 12 in width OR		
		C		30 where a new commercial use abuts		
				an existing residential use		
ID	87,120	no minimum lot	25	15 OR	30	50
_		frontage		50 where a new industrial use abuts an		
		11011110		existing residential use		
HI	no minimum lot size	no minimum lot	25	0, if there is access to rear of lot over a	15	50
***	no minimum for Size	frontage	23	drive at least 12 in width	15	
		Homuse		arryo at roust 12 m width		

⁽a) No building need provide a street line setback greater than that of the principal buildings on 3 out of 4 adjoining properties on the same side of the street.